

*Economizing Digital Case Printing:
High-Quality, Efficiency, Adaptability*



Designed for lower volume or mixed applications, the Economizer, like all Iconotech Digital Case Printers, is rugged, easy to use, and virtually maintenance free. It takes a wide range of case sizes with no adjustments. This hand-fed press easily prints 1,000 cases per hour and provides a low-cost means of printing almost any shipping container—flat cases, blanks, die cuts, or multi-wall bags.



Economizer

Digital Case Printer

The Economizer prints one side at a time, one color. The computer generated printing stencil allows exacting placement of very high resolution print anywhere within a 32" x 11" area, including text in any Windows™ font, fine-line graphics and logos, as well as consistently verifiable bar codes in a variety of symbologies.



Economizer

Digital Case Printer

Printer Specifications

General Specifications

Printer Dimensions:

- Width: 65" (1651 mm)
- Length: 28" (710 mm)
52" (1321 mm) with feeder table
- Height: 54" (1375 mm)
- Exit Height: 30" to 40" adjustable (762 to 1016 mm)

Print Specifications

Print Area:

- Width: 11" (280 mm)
- Option: 23" (584mm)
- Length: 32" (812 mm)
- Resolution: 200 dots per inch (8 dots per mm)
- Prints per Film: 2,000–5,000
- Color: Single color

Printer Capacities

Print Rate:

- Maximum: 30 cases per minute

Maximum Case Size:

- Width: 45" (1067 mm)
- Length: 40" (1016 mm); longer length possible for repeat images
- Thickness: 1/2" (13 mm)

Minimum Case Size:

- Width: 10" (254 mm)
- Length: 10" (254 mm)
- Thickness: 1/8" (3 mm) ("B" flute)
1/16" (1.5 mm) with 2-stage cylinder option

Inking System

- Type: Manual fill with dipstick level indicator



Feeder Table

Size:


- Width: 38" (965 mm)
- Depth: 24" (590 mm)

Controls

- Control Panel: Full set of controls including speed control and batch size counter which stops feed upon reaching batch count target
- Set-up: Print set-up based on box/bag length adjustable in 1/10" increments

Operating Requirements

- Electrical Supply: 120VAC, 50-60 hz., 10 amps
- Air Supply: Minimum 80 psi clean shop air
Consumption @ 60 cfm



iconotech

www.iconotech.com
e-mail: sales@iconotech.com



Resolution Technologies Corp.
Authorized International Full-Service Distributor

(800) 909-7088

www.resolution-corp.com