

Maximizing Digital Case Printing: High-Quality, Flexibility, Durability

The most flexible of the Iconotech Case Printer line, the Maximizer can print multi-wall kraft bags, flat cases, blanks, and die cuts. Its powerful vacuum feeder reliably handles all of these products and allows you to switch from one type of print job to another with ease and economy. Like all the printers in the Iconotech line, this is a rugged, long-lasting, low maintenance printer designed for ease of use as well as durability.



Maximizer

Digital Case Printer

The Maximizer prints one side at a time, one color. The computer generated printing stencil allows exacting placement of very high resolution print anywhere within a 32" x 11" area, including text in any Windows™ font, fine-line graphics and logos, as well as consistently verifiable bar codes in a variety of symbologies.



Maximizer

Digital Case Printer

Printer Specifications

General Specifications

Printer Dimensions:

Width: 65" (1651 mm)

Length: 115" (2921 mm)

Height: 59" (1500 mm)

Exit Height: 47.5" (1207 mm)

Loading Height: 17" (432 mm)

Weight: 2,000 lbs. (910 kg)

Print Specifications

Print Area:

Width: 11" (280 mm)

Option: 23" (584 mm)

Length: 32" (812 mm)

Resolution: 200 dots per inch (8 dots per mm)

Prints per Film: 5,000 maximum

Color: Single color

Printer Capacities

Print Rate (Variable):

Maximum: 50 cases or bags per minute

Maximum Case Size:

Width: 36" (915 mm)

Length: 36" (915 mm)

Thickness: 1/4" for bags

Minimum Case Size:

Width: 12" (305 mm)

Length: 18" (458 mm)

Inking System

Type: Continuous, with automatic level control

Pumps: Dual peristaltic



Feeder

Type: Vacuum pick-off system feeding from top of magazine lift table

Capacity: 12" stack height—up to 90 B flute or 60 C flute single sheet die cuts or trays or up to 100 bags depending on the bag design

Controls

Counter: Batch

Control Panel: Full set of control buttons with secondary panel on magazine

Overload: Electronic overload protection in case of jam

Operating Requirements

Electrical Supply: 240V AC, 3 phase, 50-60 hz., 20 amps

Option: 460V AC, 3 phase, 60 hz.

Air Supply: Minimum 80 psi clean shop air
Consumption @ 65 cfm



www.iconotech.com
e-mail: sales@iconotech.com

Headquarters:

1 Heritage Park Road
Clinton, CT 06413
800-521-0194

Branch:

680 Chaddick Drive
Wheeling, IL 60090-9673
847-541-2494